

Suitability for outdoor use of different combinations between polyurethane Decoral System® Powder coatings and heat transfer film Decoral System® must be assessed on www.decoral-system.com. (link: TESTED FOR OUTDOOR USE) or contacting our laboratory.

New Millennium 3D

L'idoneità all'impiego in esterno degli abbinamenti tra prodotti vernicianti poliuretanici Decoral System® e film sublimatici Decoral System® dovrà essere valutata sul sito internet www.decoralsystem.com (alla voce FINITURE ADATTE PER USO ESTERNO) oppure contattando il nostro laboratorio.

MRK-005-1125



Powder Coating: DS-0418S + Heat Transfer Film: 2117/01



Powder Coating: DS-0733S + Heat Transfer Film: 2117/03



Powder Coating: 8G-096-A009 + Heat Transfer Film: 2117/13



Powder Coating: DS 721 + Heat Transfer Film: 2117/02



Powder Coating: DS 733 + Heat Transfer Film: 2117/12



Powder Coating: DS 752 + Heat Transfer Film: 2117/23





157





298





Total duration: 12 months

EXPOSURE PERIOD

FROM: 23/05/2014

TO: 27/05/2015

LAR ID NUMBER: 94014

Colour variation (AE): 1,97 residual gloss: 86%

Technical Remarks

Excellent residual gloss and low colour variation (AE)

154

Unexposed area







EXPOSURE PERIOD:

FROM: 10/08/2022 TO: 10/08/2023

LAB ID NUMBER: 50704 POWDER COATING: 8G-096-A009 HEAT TRANSFER FILM: 2117/13 colour variation (AE): 1,56 residual gloss: 69%

Technical Remarks ood residual gloss and normal color variation (ΔΕ)

Technical Opinion: nitable for OUTDOOR USE

RECURRENEEVES
The residual gloss must be at least 20% of the original gloss. The final evaluation will be based on visual impaction with the salesd eye

Florida Test

Unexposed area (reference)

Exposed

FROM: 10/08/2022

要自

The state of the s

LAR TO NUMBER: 52706 POWDER COATING: DS 752 HEAT TRANSFER FILM: 21.17/23 colour variation (AE): 1,05 residual gloss: 86%

TO: 10/08/2023

Technical Remarks Good residual closs and normal color variation (AE)

EXPOSURE PERIOD:

uitable for OUTDOOR USE

RECOMMENTERY
The restricted gions must be at least 90% of the original gions.
The final evaluation will be based on visual inspection with
the melant eye

(reference) Exposed

Technical Opinion: uitable for OUTDOOR USE

REQUEREMENTS to residual gloss must be at least 50% of the original gloss.

Florida

0

Decoral LAB &

106









EXPOSURE PERIOD

FROM: 20/08/2013

TO: 21/08/2014

LAB. ID NUMBER: 32091
POWDER COATING: DS-04188
HEAT TRANSPER FILM: 2117/01
Colour variation (AE): 1,47
residual gloss: 95%

Technical Remarks Excellent residual gloss and low colour variation (ΔΕ)

itable for OUTDOOR USE

REQUIREMENTS

The restdual gloss must be at least 50% of the original gloss.

The final evaluation will be based on visual inspection with the maked eye



**

(reference) EXPOSURE PERIOD: FROM: 10/08/2022 TO: 10/08/2023 LAB. ID NUMBER: 91276 Technical Romarks Good residual gloss and normal color variation (ΔΕ)

necoral LAB &

Total duration 12 months

Suitable for OUTDOOR USE

REQUESTION OF THE ORDER OF THE STATE OF THE



Unexposed area

150

Unexposed area (reference) EXPOSURE PERIOD: FROM: 27/04/2019 TO: 07/05/2020 LAB. ID NUMBER: 44266 POWDER COATING: DS 795 HEAT TRANSFER FILM: 2117/12 Colour variation (AE): 2,15 residual glose: 75% Technical Remarks Good residual gloss and normal colour variation (AE) uitable for OUTDOOR USE

INITIAL PROPERTY THE PROPERTY OF THE CONTROL OF THE

Mod_TR_02_rev02 Laboratory Decoral System Date: 18/11/2014

Mod_TR_02_rev02 Laboratory Decoral System Date: 05/12/2023 ID Report: TR-NE-150-2023